DASQUAI 956






4 wheel drive Articulated Transporter

- 4-wheel drive
- Air cooled diesel engine
- 9 speeds forward . . . 3 reverse
- Speeds from .4 mph to 9.3 mph

- 3000 lb. load capacity
- Hydraulic dump
- Front differential lock
- 540 PTO . . . 750 PTO

Dasqual 956



Model 956 4 Wheel Drive Diesel Transporter Specifications

ENGINE (Diesel) Model

Lombardini 4 stroke Diesel Air Cooled

POWER TRAIN

TRANSMISSION

Sliding type key gear with synchronizer 9 speeds forward 3 reverse speeds

DIFFERENTIAL

Differential on both axles. Differential lock on front axle.

CLUTCH 8" diar

8" diameter Single dry disc

PTO

Two PTO speeds 540 rpm

540 rpm 750 rpm

CARGO BOX

3000# Capacity, 1 ft, deep x 5 ft, wide x 6½ ft, long, Sides & back hinged,

OPTIONAL

HYDRAULIC DUMP

Optional Hydraulic Jack, Dump to the rear or either side.

Optional Hydraulic Kit for dump. Gear type pump, 3:1, GPM, 1500 PSI.

STEERING

Articulated in center with worm gear oil bath steering.

ELECTRICAL

 Battery
 ...
 12 volt, 92 amp hour

 Starter
 ...
 12 volt

 Headlights
 ...
 2

 Running lights
 ...
 2 Front

 2 Rear

BRAKES

Mechanical brakes on rear axle. Hand brake also comes as standard equipment—it operates independent of the main braking system.

MPH at rated engine RPM (3000)

| | Range | Gear | MPH |
|---------|--------|---------|------|
| Speeds: | Low | 1st | .40 |
| | | 2nd | .68 |
| | | 3rd | 1.12 |
| | | Reverse | .99 |
| | Medium | 1st | 1.50 |
| | | 2nd | 1.80 |
| | | 3rd | 2.67 |
| | | Reverse | 2.67 |
| | High | 1st | 3.91 |
| | (-D) | 2nd | 4.16 |
| | | 3rd | 9.32 |
| | | Reverse | 6.21 |

DIMENSIONS

| THE LACT | | |
|----------|-----------|--------|
| Wheel | Base | 90½" |
| Maximi | um Height | 42" |
| Length | | 15634" |
| | | |
| | | |
| (Front | & Rear) | |

WHEEL WIDTH

FRONT, 251/4

REAR, 33

Centerline to centerline

The above specifications are subject to change without notice.

PASQUALI U.S.A. INC.

. 116 PAOLI ST. P.O. BOX 7 VERONA, WI 53593 (608) 845-6438