# DASILAI 971




### 4 wheel drive FRONT WHEEL STEERING

The Model 971 offers conventional front wheel steering with those same attractive features included in the Pasquali Articulated line. Compact power coupled with operational efficiency and fuel economy make it a top competitor with larger more expensive tractors. The quality built in the Pasquali tractors guarantee hundreds of hours of trouble-free economical performance in a wide range of applications. Some of the features of this tractor are:

- 4-Wheel drive
- Air-cooled diesel
- Front differential lock
- Front wheel steering

- 9 speeds forward . . . 3 reverse
- Ground speeds .37 to 15.2 mph
- 540 PTO, 750 PTO, ground speed PTO
- Over 150 implements to fit tractors

## DASQUAI 971



### Model 971 4-Wheel Drive Diesel Tractor Specifications

#### ENGINE (Diesel) Model

 Ruggerini
 4 stroke Diesel

 Air Cooled
 35 SAE H.P.

 Brake horsepower
 3000 rpm

 Fuel economy
 2300 rpm

 Peak torque
 2300 rpm

 No. cylinders
 2

 Displacement
 68.6 in³

 Bore and stroke
 3.64 x 3.68 in.

#### POWER TRAIN

TRANSMISSION

Sliding type key gear with synchronizer.

9 speeds forward

3 reverse speeds

DIFFERENTIAL

Differential on both axles. Differential lock on front axle.

CLUTCH

8" diameter

Single dry disc

PTO

Two PTO speeds

540 rpm

750 rpm

PTO can also be synchronized with all tractor speeds.

#### HYDRAULIC LIFT

Independent hydraulic lift system.
Direct drive, gear type pump.
Hitch......3-point linkage
System......Category I
Position control.......Yes
Remote valve......Optional

#### STEERING

Conventional front steering with worm gear oil bath steering. Power steering optional full hydraulic control.

#### ELECTRICAL

Battery ..... 12 volt, 92 amp hour Starter ..... 12 volt Headlights ..... 2 Running lights ..... 2 Front 2 Rear

#### BRAKES

Independent, separate, mechanical brakes on rear wheels. Hand brake also comes as standard equipment — it operates independent of the main braking system.

#### MPH at rated engine RPM (3000)

	Range	Gear	MPH					
Speeds:	Low	1st	.37					
		2nd	.62					
		3rd	1.43					
		Reverse	verse .93 1st 1.06 2nd 1.68					
	Medium	Medium 1st						
		2nd	1.68					
		3rd	3.73					
		Reverse	2.55					
	High	1st	4.23					
		2nd	6.84					
		3rd	15.22					
		Reverse	10.25					

#### DIMENSIONS

Wheel Base	
Maximum Heigi	ht 43 ½ "
Length	961/2"
Weight	2002 lbs
Tires	Rear 9.50 x 20
	Front 7.50 x 18

#### TREAD ADJUSTMENT

Minimum.	•			*			•									49
Maximum								1	-			+				62
(variable in	10	:1	ŧ	19	n	e	1	'n	5	1						

The above specifications are subject to change without notice.